

This listing of claims will replace all prior versions, and listings, of claims in the application:

Listing of Claims:

1. (previously presented): A Foley catheter (10) with a proximal end (22) and a distal end (23), an elastomeric reservoir bulb (21) at the proximal end for storing fluid under pressure and in readiness to inflate, an anchoring balloon (20) at the distal end a lumen (12) connecting the reservoir bulb and the balloon for flow of fluid from the bulb to the balloon when the device is used, and including a control device (25) at the proximal end of the lumen to prevent said flow until said flow is desired

said control device (25) comprises a plug (26) which blocks the lumen at its proximal end and includes a parting line, which enables the plug to be parted into two separate parts, by manual manipulation from outside the lumen, such parting having the effect of opening up fluid communication along the lumen from the reservoir bulb (21) to the balloon (20) to fully fill the balloon

wherein the plug further comprises a co-axial stem (27) and annular part (26) with a diameter at least twice that of the stem, which meet at said parting line wherein the annular part comprises a tapering portion displaying a small end and a large end, the small end being remote from the stem, wherein the annular part comprises a cylindrical portion, wherein the cylindrical portion lies between the tapering portion and the stem, in the axial direction of the plug, wherein the diameter of the cylindrical portion is greater than that of the large end of the tapering portion, including a step between the large end of the tapering portion and the cylindrical portion.

2. (original): Device as claimed in claim 1 wherein the bulb (21) is coated with a substance to inhibit the passage of the fluid through the wall thickness of the bulb.

3. (original): Device as claimed in claim 2 wherein the coating is on the outside of the bulb wall thickness.

4. (original): Device as claimed in claim 2 wherein the coating is on the inside surface of the bulb wall.

5. (original): Device as claimed in claim 1 wherein the plug (26) carries a fluid-tight skirt membrane which extends proximally from the proximal end face of the plug.

6. (cancelled):

7. (cancelled):

8. (cancelled):

9. (cancelled):

10. (cancelled):

11. (cancelled):

12. (cancelled):

13. (cancelled):

14. (cancelled):

15. (cancelled):

16. (previously presented): Device as claimed in claim 1, wherein the diameter of the annular part of the plug is at least three times that of the stem.

17. (original): Device as claimed in claim 16 wherein the annular part comprises an annulus (26) of material with a proximal end face (30) and a distal end face (28) and a bore (29) extending between the two end faces.

18. (previously presented): Device as claimed in either one of claims 16 or 17, wherein said stem (27) extends proximal of the annular port, coaxially therewith and has an outside diameter substantially less than that of said annular port (26).

19. (original): Device as claimed in claim 18 wherein the stem is friction fitted within the bore (29) of the annular part.

20. (original): Device as claimed in claim 18 wherein the stem (27) is integral with the annular part and joined to it by a circle of weakness (31).

21. (original): Device as claimed in claim 20 wherein the annular part and stem are together formed as only one piece of molded polymer material.

22. (previously presented): Device as claimed in claim 16, wherein the axial length of the annular part of the plug is greater than its largest diameter.

23. (previously presented): Device as claimed in either one of claims 1 or 16, wherein the length of the cylindrical portion is smaller than its radius.

24. (previously presented): Device as claimed in either one of claims 1 or 16, in which the tapering portion comprises a frusto-conical or substantially frusto-conical portion which has a small end which is larger than the small end of the tapering portion.

25. (cancelled):

26. (previously presented): Device as claimed in claim 24 wherein the tapering portion comprises first and second frusto-conical or substantially frusto-conical portions, of different cone angle, such that the diameter of the tapering portion varies along the axis at a greater rate near the small end of the tapering portion than at the large end of the tapering portion.

27. (previously presented): Device as claimed in claim 1 in which the stem is cylindrical.

28. (previously presented): Device as claimed in claim 1 wherein the fluid supply element (21) has an open proximal end (22) closed by a filler valve (24).

29. (cancelled).

30. (cancelled).

31. (cancelled).

32. (cancelled).

33. (cancelled).

34. (cancelled):

35. (previously presented): Apparatus as claim in claim 1 wherein the elastomeric bulb is sleeved in shrink-wrap material.

36. (previously presented): Apparatus as claimed in either one of claims 34 or 35 wherein the permeability of the sleeve material to diffusion of water therethrough is less than that of latex rubber.

37. (previously presented): Apparatus as claimed in either one of claims 34 or 35 wherein the shrink-wrap material is polystyrene.

38. (previously presented): Apparatus as claimed in either one of claims 34 or 35 wherein the shrink-wrap sleeve incorporates a tear strip.

39. (cancelled).

40. (cancelled).

41. (cancelled).

42. (cancelled).

43. (cancelled).

44. (cancelled).

45. (cancelled):

46. (cancelled):